



Point of Use Water Coolers

Atlantis Series

A solid POU cooler with a contemporary look that offers quality, reliability and easy serviceability.

Model:

POUD1SHS (Hot N' Cold™)

POUD1SK (Cook N' Cold™)

- POU does not include water treatment
- Stylish, rounded front, contemporary design
- Non-removable 300 series stainless steel reservoir
- Dual float system with built-in safety float to prevent overflowing
- Bright white or black polyethylene cabinet won't dent or rust
- 2 piece hot tank easy to service
- Tough, durable, large drip tray
- Handle on back enables easy transport and placement
- Available in Cook N' Cold™ and Hot N' Cold™
- 3 year limited warranty



Atlantis Series Technical Data & Specifications



Dimensions:
W 13" x D 12 13/16" x H 38 11/16"

Net Weight (approx.):
POUD1SK (Cook N' Cold™) - 50 lbs.
POUD1SHS (Hot N' Cold™) - 55 lbs.

Cabinet: The stylish, one-piece, bright white polyethylene cabinet hides scratches, fingerprints and won't dent or rust. Holes are pre-drilled on cabinet side for installation of cup dispenser.

Cold Water Refrigeration Unit: Convection cooled condenser. Internally, spring mounted, hermetically sealed compressor with automatic overload protector. No lubrication needed. Refrigerant is controlled accurately by a capillary tube.

Cold Water Thermostat: Temperature is controlled by an adjustable thermostat with "Off" position that is easily accessible on the rear of the unit.

Cold Water Reservoir: Type 300 series stainless steel. External copper refrigerant coil. Encased in pre-fitted molded plastic foam insulation.

2 Piece Hot Water Tank: The 500 watt heating element can be replaced on site reducing time and service costs. 2 piece hot tank is easy to replace or service without breaking soldered refrigeration connections. The hot tank is type 300 series stainless steel.

Hot Water Capacity: 45 x 6 oz cups of piping hot water per hour. 1 1/2 quart storage tank.

Hot Water Thermostat: Adjustable thermostat with safety limiter.

Hot Water Safer Faucet: Self closing faucet requires a two-step action that is easy for adults to use, but helps to protect small children. Faucets are made of durable polypropylene.

Cold Water Capacity Table			
Room Temp	Water Temp	Gallons per hour of 50°F Water	# of 3oz cups per hour
70°F	70°F	1.4	59
80°F	80°F	1.0	42
90°F	90°F	0.6	25
100°F	100°F	0.4	17

Float System: Dual mechanical floats include a safety lockout.

Drip Receptor: Drip tray lifts out for easy removal. Molded for durability, dishwasher safe.

Electrical: 115 volts, 60 Hertz. Water cooler compressor 1/20 hp. Three wire service cord and polarized plug furnished.

Warranty: (Within the Continental Limits of the United States and Canada) Limited three year warranty. Three years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample copy available upon request.

Components in this water cooler are lead free as defined by the Safe Drinking Water Act Amendments of 1986 and the Lead Contamination Control Act of 1988. Model Listed by Underwriter's Laboratories to U.S. and Canadian Standards.



Specifications are subject to change without notice.

©2009 OASIS International. OASIS® and the palm tree design are registered trademarks of OASIS International. Hot N' Cold™ and Cook N' Cold™ are trademarks of OASIS International.